

IN THE CLAIMS

~~Claims~~ 1-73. (Cancelled)

74. (New) A composite material comprising:

a. a material comprising a welding fabric welded to a first substrate, wherein said welding fabric comprises a welding portion and a fixing portion, wherein said welding portion includes a material which melts under hot pressing conditions and said fixing portion is provided with auxiliary fixing means;

b. wherein said fixing portion contains auxiliary fixing means comprising holes bored into the fixing portion or straps attached to the fixing portion through which a rope or cord is threaded;

c. wherein the welding portion extends across part of the width of the welding fabric; and

d. a second substrate to which said material is fixed by said auxiliary fixing means.

75. (New) A composite material comprising:

a. a material comprising a welding fabric welded to a first substrate, wherein said welding fabric comprises a welding portion and a fixing portion, wherein

said welding portion includes a material which melts under hot pressing conditions and said fixing portion is provided with auxiliary fixing means;

b. wherein said fixing portion contains auxiliary fixing means comprising holes bored into the fixing portion or straps attached to the fixing portion through which a rope or cord is threaded;

c. wherein the welding portion is at each end of the width of the welding fabric; and

d. a second substrate to which said material is fixed by said auxiliary fixing means.

76. (New) A composite material comprising:


a. a material comprising a welding fabric welded to a first substrate, wherein said welding fabric comprises a welding portion and a fixing portion, wherein said welding portion includes a material which melts under hot pressing conditions and said fixing portion is provided with auxiliary fixing means;

b. wherein said fixing portion contains auxiliary fixing means comprising holes bored into the fixing portion or straps attached to the fixing portion through which a rope or cord is threaded;

c. wherein the welding portion is in the middle portion of the welding fabric; and

d. a second substrate to which said material is fixed by said auxiliary fixing means.

77. (New) A composite material comprising:



a. a material comprising a welding fabric welded to a first substrate, wherein said welding fabric comprises a welding portion and a fixing portion wherein said welding portion includes a material which melts under hot pressing conditions and said fixing portion is provided with auxiliary fixing means;

b. wherein said auxiliary fixing means is provided with straps through which a rope can be threaded;

c. wherein the welding portion is in the middle of the welding fabric; and

d. a second substrate to which said material is fixed by said auxiliary fixing means.

78. (New) A composite material comprising:

a. a material comprising a welding fabric welded to a first substrate, wherein said welding fabric comprises a welding portion and a fixing portion, wherein

said welding portion includes a material which melts under hot pressing conditions and said fixing portion is provided with auxiliary fixing means;

- b. wherein said auxiliary fixing means is provided with straps through which a rope can be threaded;
- c. wherein the welding portion is at each end of the welding fabric; and
- d. a second substrate to which said material is fixed by said auxiliary fixing means.

79. (New) A composite material comprising:

- a. a material comprising a welding fabric welded to a first substrate, wherein said welding fabric comprises a welding portion and a fixing portion' wherein said welding portion includes a material which melts under hot pressing conditions and said fixing portion is provided with auxiliary fixing means;
- b. wherein said auxiliary fixing means is provided with straps through which a rope can be threaded;
- c. wherein the welding portion extends across part of the width of the welding fabric; and
- d. a second substrate to which said material is

In re Appl. No. 09/033,909
Confirmation No. 2662

JH fixed to said auxiliary fixing means.
